

AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT			1. CONTRACT ID CODE	PAGE OF PAGES	
2. AMENDMENT/MODIFICATION NO. 0002		3. EFFECTIVE DATE 25-Jun-2003	4. REQUISITION/PURCHASE REQ. NO.		5. PROJECT NO.(If applicable)
6. ISSUED BY USACE, CONTRACTING DIVISION ATTN: CEMVN-CT, RM 172 7400 LEAKE AVE. NEW ORLEANS LA 70118		CODE DACW29	7. ADMINISTERED BY (If other than item 6) <b>See Item 6</b>		
8. NAME AND ADDRESS OF CONTRACTOR (No., Street, County, State and Zip Code)			X	9A. AMENDMENT OF SOLICITATION NO. DACW29-03-B-0060	
			X	9B. DATED (SEE ITEM 11) 15-May-2003	
				10A. MOD. OF CONTRACT/ORDER NO.	
				10B. DATED (SEE ITEM 13)	
CODE		FACILITY CODE			
11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS					
<input checked="" type="checkbox"/> The above numbered solicitation is amended as set forth in Item 14. The hour and date specified for receipt of Offer <input type="checkbox"/> is extended, <input type="checkbox"/> is not extended. Offer must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended by one of the following methods: (a) By completing Items 8 and 15, and returning _____ copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) By separate letter or telegram which includes a reference to the solicitation and amendment numbers. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment you desire to change an offer already submitted, such change may be made by telegram or letter, provided each telegram or letter makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.					
12. ACCOUNTING AND APPROPRIATION DATA (If required)					
13. THIS ITEM APPLIES ONLY TO MODIFICATIONS OF CONTRACTS/ORDERS. IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14.					
A. THIS CHANGE ORDER IS ISSUED PURSUANT TO: (Specify authority) THE CHANGES SET FORTH IN ITEM 14 ARE MADE IN THE CONTRACT ORDER NO. IN ITEM 10A.					
B. THE ABOVE NUMBERED CONTRACT/ORDER IS MODIFIED TO REFLECT THE ADMINISTRATIVE CHANGES (such as changes in paying office, appropriation date, etc.) SET FORTH IN ITEM 14, PURSUANT TO THE AUTHORITY OF FAR 43.103(B).					
C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED INTO PURSUANT TO AUTHORITY OF:					
D. OTHER (Specify type of modification and authority)					
E. IMPORTANT: Contractor <input type="checkbox"/> is not, <input type="checkbox"/> is required to sign this document and return _____ copies to the issuing office.					
14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organized by UCF section headings, including solicitation/contract subject matter where feasible.) The above numbered solicitation for Atchafalaya Basin Levees, W85 - A & B Levee Enlargement, Station 4266+00 to Station 4503+00 Competitive 8(a), Iberia and St. Mary Parishes, Louisiana is hereby amended as follows:  BID OPENING DATE Bid Opening date and time of 16 July 2003, 2:00 P.M., local time at place of bid opening, is hereby established.					
Except as provided herein, all terms and conditions of the document referenced in Item 9A or 10A, as heretofore changed, remains unchanged and in full force and effect.					
15A. NAME AND TITLE OF SIGNER (Type or print)			16A. NAME AND TITLE OF CONTRACTING OFFICER (Type or print)		
			TEL: _____ EMAIL: _____		
15B. CONTRACTOR/OFFEROR  (Signature of person authorized to sign)		15C. DATE SIGNED	16B. UNITED STATES OF AMERICA  BY _____ (Signature of Contracting Officer)		16C. DATE SIGNED 18-Jun-2003

## SECTION SF 30 BLOCK 14 CONTINUATION PAGE

SECTION 00700

Page 69, 52.236-4 PHYSICAL DATA, subparagraph (c). Delete the 2<sup>nd</sup> sentence and replace with: "Proceed westward across the floodgate bridge. The bridge has a clear roadway width of 10 feet 6 inches. The load limit on the bridge is 20 tons (HS20-44)."

SECTION 00010

Delete page00010-3 in its entirety and replace with the attached revised page 00010-3 therefor.

SECTION 02077

1. Pages a and 1. Change the title of the section to "Geotextile Separator Under Rock Berm and Ramps."
2. Page 1, paragraph 1.1. In the 3<sup>rd</sup> line, change "levee crown road" to "rock berm"
3. Page 2, paragraph 3.1. Delete the 3<sup>rd</sup> sentence in its entirety and substitute the following therefore: "Any shell, crushed stone, or other road base material shall be removed from ramps until a firm soil base is established to place the geotextile on. Existing Rock berm material shall not be removed."
4. Page 4, Table 1: Rename the Table, "GEOTEXTILE SEPARATOR FOR ROCK BERM AND RAMPS"

SECTION 02231

1. Page 2, paragraph 3.2.1. In the 4<sup>th</sup> line, change "02332-3.1.2" to "02318-3.1.2.1".
2. Page 4, paragraph 3.3.2.1. In the 3<sup>rd</sup> line from the end of this paragraph, change "02332-3.1.2" to "02318-3.1.2.1".
3. Page 4, paragraph 3.4.1. Line 2, after "pit" insert ", chipping as limited in paragraph 3.4.3, or burning as limited in paragraph 3.4.4".
4. Page 5, paragraph 3.4.3. Line 2, change "either to stockpiles indicated on the drawings or to other," to "to".
5. Page 5. After paragraph 3.4.3, add the following new subparagraph:

"3.4.4 Burning

The Contractor shall comply with the applicable pollution restrictions of Title 40 Code of Federal Regulations, Part 76 and Louisiana Air Control Commission, effective 17 July 1972,

amended November 1972 (Act 1964, No. 259, Title 40, Section 2201). Subject to such restrictions and obtaining any permit which may be required by said commission, the Contractor may burn material within the contract area, and at any time within the contract period. Burning operations shall be conducted so as to prevent damage to standing timber or other flammable growth. The Contractor shall be responsible for any damage to life and/or property resulting from fires that are started by its employees or as a result of its operations. The Contractor shall furnish, at the site of burning operations, adequate fire fighting equipment to properly equip its personnel for fighting fires. Fires shall be guarded at all times and shall be under constant surveillance until they have been extinguished. Debris resulting from burning operations shall be buried in the borrow pit, in accordance with paragraph 3.4.2.”

#### SECTION 02332

Page 8, paragraph 3.1.1. In the 5<sup>th</sup> line, change “paragraphs 3.1.2” to “02318-3.1.2.1”.

#### SECTION 02381

Page 2, paragraph 1.3.2.2. In the 1<sup>st</sup> sentence, change “per ton for “Stone”.” to “per ton for “Armor Stone”.”

#### SECTION 02731

1. Page 2, paragraph 1.3.1. Delete the words “new road” from the paragraph heading and the first sentence.
2. Page 3, paragraph 1.4.1: Delete the words “new road” from the paragraph heading and the first sentence.

#### SECTION 02922

1. Page 3. Delete “1.9 RESERVED” in its entirety and substitute the following therefore.

#### “1.9 SPECIAL EQUIPMENT

##### 1.9.1 Mulch Spreader

The mulch spreader used for applying straw or hay mulch shall be equipped with a blower that is capable of discharging hay or straw mulch material through a discharge spout at speeds up to 220-feet per second. The discharge spout shall be capable of 360-degree horizontal rotation and have a minimum of 60-degree range of elevation and depression. The mulch spreader shall be equipped with an asphalt adhesive supply and application system, near the discharge end of the boom spout, that is capable of applying an asphalt adhesive in atomized form to the mulch material at a predetermined rate. The spreader shall be capable of blowing the adhesive-coated mulch over the surface of a graded or otherwise prepared slope at a uniform rate, forming a porous, stable, erosion-resisting cover at a distance of not less than 100-feet.

## 1.9.2 Wood Cellulose Fiber Mulch Spreader or Recycled Wood Pulp

Hydraulic equipment used for the application of slurry of prepared wood pulp shall have a built-in agitation system with an operating capacity sufficient to agitate, suspend, and homogeneously mix a slurry containing up to 300 pounds of fiber for each 1000 gallons of water. The slurry distribution lines shall be large enough to prevent stoppage. The discharge line shall be equipped with hydraulic spray nozzles that will provide even distribution of the slurry on the various slopes to be mulched. The slurry tank shall have a minimum capacity of 1,000 gallons and shall be mounted on a traveling unit, which may be either self-propelled or drawn by a separate unit, that will place the slurry tank and spray nozzles near the areas to be mulched so as to provide uniform distribution without waste. The Contracting Officer may authorize equipment with a smaller tank capacity provided that the equipment has the necessary agitation system and sufficient pump capacity to spray the slurry in a uniform seat over the surface of the area to be mulched.”

2. Page 5. After paragraph 2.1.5, add the following new subparagraph:

### “2.1.5.1 Wood Cellulose Fiber or Recycled Wood Pulp Mulch

If the wood cellulose fiber option is used, the wood cellulose fiber mulch with tackifier for use with hydraulic application equipment shall consist of wood cellulose fiber. If the recycled wood pulp mulch option is used, the recycled wood pulp mulch for use with hydraulic application equipment shall consist of pulped ecology by-product made from printer's scrap paper, which contains wood cellulose and kaolin clay to provide non-toxic organic tackifier. The mulch shall be processed to contain no growth or germination inhibiting factors, and dyed an appropriate color to facilitate visual metering of application of the materials. The mulch material shall be supplied in packages having a net weight not in excess of 100 pounds. The wood cellulose mulch fiber shall contain not in excess of 10 percent moisture, air dry weight basis. The wood cellulose mulch fiber shall be manufactured so that after addition and agitation in slurry tanks, with water, and any other additives, the fibers in the material will become uniformly suspended to form a homogeneous slurry, and that when hydraulically sprayed on the ground, the material will form a blotter like ground cover which, after application, will allow the absorption of moisture and allow rainfall or mechanical watering to percolate to the underlying soil. The Contractor shall be prepared to submit, on request, certification from the supplier that laboratory and field testing of the product has been accomplished, and that the product meets the foregoing requirements.”

## DRAWINGS

Delete Dwgs. 3, 4, 5, 8, 9, and 15 of 52 in their entirety and substitute the attached revised Dwgs. 3, 4, 5, 8, 9, and 15 of 52 therefore.

## SECTION 00010 - BIDDING SCHEDULE

ATCHAFALAYA BASIN LEVEES  
W85 – A & B LEVEE ENLARGEMENT  
STAS. 4266+00 to 4503+00  
IBERIA AND ST. MARY PARISHES, LA

Item	Description	Estimated Quantity	Unit	Unit Price	Estimated Amount
0001	Mobilization and Demobilization	1	LS		
0002*	Geotextile Separator	4,000	SY		
0003	Clearing and Grubbing	1	LS		
0004	Embankment, Compacted Fill	215,656	CY		
000*5	Embankment, Uncompacted Fill	67,500	CY		
0006*	Surfacing	6,500	CY		
0007	Silt Fencing	47,400	LF		
0008*	Fertilizing, Seeding and Mulching	85	Acre		
0009	Armor Stone	3,210	Ton		
0010	Truck Wash-Down Rack	1	LS		
TOTAL:					\$

Award will be made as a whole to one bidder.

\* Denotes A Change From The Previous Bid Schedule

00010-5

ED 99-010